

# K-T-STUECKE AG IG AG

Tees, male-female-male

**HANSA FLEX**

## Caracteristici

|                      |                              |
|----------------------|------------------------------|
| Presiune de lucru    | 60 bar                       |
| Temperatura de lucru | Max. 150 °C                  |
| Filet interior       | Parallel to DIN EN ISO 228-1 |
| Material             | Alamă nichelată              |
| Filet exterior       | conical acc. DIN 2999        |



## Indicație

Alte date sunt disponibile la cerere.

## Articol

| Denumire       | Filet   | L1<br>(mm) | L2<br>(mm) | Deschiderea cheii fixe |
|----------------|---------|------------|------------|------------------------|
| K- 07 40 48 95 | G/R 1/8 | 37,0       | 21,0       | 10 mm                  |
| K- 07 40 48 96 | G/R 1/4 | 47,0       | 25,5       | 13 mm                  |
| K- 07 40 48 97 | G/R 3/8 | 52,0       | 28,0       | 17 mm                  |
| K- 07 40 48 98 | G/R 1/2 | 62,0       | 33,5       | 21 mm                  |
| K- 07 40 48 99 | G/R 3/4 | 66,5       | 36,5       | 25 mm                  |
| K- 07 40 49 00 | G/R 1   | 78,0       | 45,0       | 30 mm                  |