

K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA FLEX

Caracteristici

| | |
|----------------------|--|
| Tip de racord | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Temperatura de lucru | -40 °C to +74 °C |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Nu este adecvat pentru unelte cu percuție sau cu pulsații!

Articol

| Denumire | Ø furtun interior (mm) | Ø furtun exterior (mm) | Ø spiră exterioară (mm) | Max. working pressure resistance at 23°C (bar) | Lungime max. de lucru (m) |
|----------------|------------------------|------------------------|-------------------------|--|---------------------------|
| K- 07 10 12 71 | 5,0 | 8,0 | 40 | 10 | 3,0 |
| K- 07 10 12 73 | 5,0 | 8,0 | 40 | 10 | 6,0 |
| K- 07 10 12 75 | 5,0 | 8,0 | 40 | 10 | 7,5 |
| K- 07 10 12 80 | 6,3 | 9,5 | 60 | 10 | 3,0 |
| K- 07 10 12 82 | 6,3 | 9,5 | 60 | 10 | 6,0 |
| K- 07 10 12 84 | 6,3 | 9,5 | 60 | 10 | 7,5 |
| K- 07 10 12 78 | 6,3 | 9,5 | 60 | 10 | 10,0 |
| K- 07 10 12 89 | 8,0 | 12,0 | 80 | 9 | 3,0 |
| K- 07 10 12 91 | 8,0 | 12,0 | 80 | 9 | 6,0 |
| K- 07 10 12 93 | 8,0 | 12,0 | 80 | 9 | 7,5 |
| K- 07 10 12 87 | 8,0 | 12,0 | 80 | 9 | 10,0 |

Accesorii

K-DREHBARE VERSCHRAUBUNG Swivel adapters