

# K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

**HANSA FLEX**

## Caracteristici

Strat interior	Soft-PVC, red, oil resistant
Insertie	Împletitură din poliester
Strat exterior	Soft-PVC, black, oil resistant
Temperatură	-20 °C to +60 °C
Lungimea rolelor	50 m



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

## Articol

Denumire	Ø furtun interior (mm)	Ø furtun exterior (mm)	Max. working pressure resistance at 23°C (bar)	Rază min. de îndoire (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120