

# K-W STECK VB 2-FACH WAND 20-63 INFI

2-fold angle connector Ø 20 mm - Ø 63 mm with wall mounting  
(adjustable)

**HANSA FLEX**

## Caracteristici

Medii	Compressed air, vacuum, inert gases
Presiune de lucru	-0,99 bar - 15 bar
Domeniu de temperaturi	-20 °C to +80 °C
Garnitură de etanșare	NBR
Carcasă	Nickel-plated brass
Inel de fixare	Stainless steel 1.4301
Piuliță	Nickel-plated brass
Inel O	NBR
Inele de siguranță	Technopolymer



## Articol

Denumire	Ø exterior țeavă	Racord	B	C	E	I	L1	L2	L max (mm)	L min (mm)	M	N	O	P	Deschiderea cheii 1 (mm)	Deschiderea cheii 2 (mm)
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)			(mm)	(mm)	(mm)	(mm)		
K- 07 40 54 14	20 mm	G 1/2"	31,5	20,0	34,5	28,5	27,0	51,5	54	22	74	61	30,5	5	26	30
K- 07 40 54 15	25 mm	G 1/2"	38,5	21,0	42,5	28,5	27,0	59,0	54	22	74	61	30,5	5	26	35