

K-DIGIT DRUCKSCHA H 3DURCHF IA PF2A

Digital Flow Switch PF2A

HANSA FLEX

Caracteristici

Tip constructiv	Digital Flow Switch
presiune max. de lucru	0,1 MPa
Tensiune nominală	24 V DC
Afișaj de funcționare	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
Cablu de pornire/oprire	without connection cable
Tip de protecție	IP 65
Temperatură mediu	0 °C to +50 °C
Temperatură ambiantă	0 °C to +50 °C
Medii	Air and nitrogen
Serie	PF2A
Alte date	for High flow Integrated Display Type



Descriere

Digital flow switch for high flow, series PF2A, for air and nitrogen, with integrated display unit, measuring range 150 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. ±2% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (1 to 5 V), with function to switch over the display unit, supply voltage 24 V DC, protection class IP 65, connection cable not included, connection size G 1 1/2

Articol

Denumire	Filet de conectare	Semnal de ieșire	Unitate de reglare [Min] (L/min)	Domeniu de măsurare	Presiune de lucru min. (MPa)	Tensiune nominală / tip curent	Consum de curent max. (mA)	Precizia repetării
K-07 50 00 28	G 1	PNP + Analog output (1-5V)	5,00	150 bis 3000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 29	G 1	PNP + Analog output (4-20mA)	5,00	150 bis 3000 l/min	1,50	-	150	max. ±3 % from scale
K-07 50 00 31	G 1 1/2	PNP + Analog output (1-5V)	10,00	300 bis 6000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 32	G 1 1/2	PNP + Analog output (4-20mA)	10,00	300 bis 6000 l/min	1,50	-	150	max. ±3 % from scale
K-07 50 00 36	G 2	PNP + Analog output (1-5V)	10,00	600 bis 12000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K-07 50 00 37	G 2	PNP + Analog output (4-20mA)	10,00	600 bis 12000 l/min	1,50	-	150	max. ±3 % from scale