

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Caracteristici

| | |
|------------------------|--|
| presiune max. de lucru | 0,7 MPa |
| Presiune de lucru min. | 0.10 MPa |
| Execuție | rack and pinion |
| Temperatură mediu | 0 °C to +60 °C |
| Temperatură ambiantă | 0 °C to +60 °C |
| Unghi de pivotare | 0 to 190° |
| Medii | Aer comprimat |
| Serie | MSQ |
| Alte date | narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible |



Articol

| Denumire | Ø piston (mm) | Racord pneumatic | Dimensiunea constructivă | Amortizare | Greutate per m (kg) |
|----------------|---------------|------------------|--------------------------|---|---------------------|
| K- 07 55 01 13 | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| K- 07 55 01 18 | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| K- 07 55 01 21 | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| K- 07 55 01 26 | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| K- 07 55 01 11 | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| K- 07 55 01 16 | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| K- 07 55 01 19 | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| K- 07 55 01 22 | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| K- 07 55 01 24 | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| K- 07 55 01 09 | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| K- 07 55 01 14 | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| K- 07 55 01 12 | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| K- 07 55 01 17 | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| K- 07 55 01 20 | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| K- 07 55 01 23 | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| K- 07 55 01 25 | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| K- 07 55 01 10 | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| K- 07 55 01 15 | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |