

K-ROHRLEIT ALU KALIBRIERT GRAU INFI

Pipe made of aluminium, calibrated, grey

HANSA FLEX

Caracteristici

Medii	Compressed air, vacuum, inert gases
Coefficient de dilatare	0,024 mm/m °C
Presiune de lucru	-0,99 bar - 15 bar
Domeniu de temperaturi	-20 °C to +80 °C
Culoarea	greyRAL 7035
Material	Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2
Tratarea suprafeței	electrostatic coating



Indicații referitoare comandă

Special lengths on request

Articol

Denumire	Ø exterior (mm)	Grosimea peretelui (mm)	Greutate per m (kg)	Masă specifică per dm ³ (kg)	Lungime (m)	Unitate de ambalaj
K- 07 40 53 15	20	1,5	0,235	2,7	4,000	1 piece
K- 07 40 53 30	20	1,5	0,235	2,7	6,000	1 piece
K- 07 40 53 16	25	1,5	0,298	2,7	4,000	1 piece
K- 07 40 53 31	25	1,5	0,298	2,7	6,000	1 piece
K- 07 40 53 17	32	1,5	0,387	2,7	4,000	1 piece
K- 07 40 53 32	32	1,5	0,387	2,7	6,000	1 piece
K- 07 40 53 18	40	1,5	0,490	2,7	4,000	1 piece
K- 07 40 53 33	40	1,5	0,490	2,7	6,000	1 piece
K- 07 40 53 19	50	2,0	0,814	2,7	4,000	1 piece
K- 07 40 53 34	50	2,0	0,814	2,7	6,000	1 piece
K- 07 40 53 20	63	2,0	1,034	2,7	4,000	1 piece
K- 07 40 53 35	63	2,0	1,034	2,7	6,000	1 piece
K- 07 40 55 08	80	2,0	1,493	2,7	4,000	1 piece
K- 07 40 55 10	80	2,0	1,493	2,7	6,000	1 piece
K- 07 40 53 21	110	2,5	2,280	2,7	4,000	1 piece
K- 07 40 53 36	110	2,5	2,280	2,7	6,000	1 piece