

# K-SV 6 4 HOSTA

Bulkhead connectors Hosta

**HANSA FLEX**

## Caracteristici

Presiune de lucru	Max. 16 bar (at +20 °C)
Temperatura de lucru	-20 °C to +70 °C
Material	Alamă nichelată
Inel de presiune	Hostaform (black nickel-plated for Ø 10, 12)
Inel O	NBR, siliconefree
Clește de prindere	Stainless steel AISI 316



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Articol

Denumire	Filet	pentru Ø exterior furtun	L1 (mm)	Deschiderea cheii fixe
K- 07 40 29 57	M 10 x 1	4 mm	32,0	13 mm
K- 07 40 29 58	M 14 x 1	6 mm	33,5	17 mm
K- 07 40 29 59	M 16 x 1	8 mm	37,0	18 mm
K- 07 40 29 60	M 17 x 1	10 mm	39,5	20 mm
K- 07 40 29 61	M 20 x 1	12 mm	42,0	24 mm