

# LKM IR ST DK

Mufă - cuplaj de conectare (aer) cu element de siguranță

**HANSA FLEX**

## Caracteristici

Tip constructiv	Mufă pentru cuplaj cu închidere rapidă
Racord 1	Filete cilindrice interioare BSP
Racord 2	
Presiune de lucru	max. 12 bari
Debit aer	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatură mediu	-20 °C to +70 °C
Carcasă	Aluminium, anodised
Filet	Nickel-plated brass
Piese interioare	Stainless steel
Buton, supapă	Hardened, galvanised steel
Material de etanșare	NBR



## Indicație

Not suitable for hitting / pulsating tools.  
Alte date sunt disponibile la cerere.

## Descriere

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Articol

Denumire	Filet de conectare	Racord	Lungime (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24