

# LKM IR ST DK

Mufă - cuplaj de conectare (aer) cu element de siguranță

**HANSA FLEX**

## Caracteristici

<b>Tip constructiv</b>	Mufă pentru cuplaj cu închidere rapidă
<b>Racord 1</b>	Filete cilindrice interioare BSP
<b>Racord 2</b>	
<b>Presiune de lucru</b>	max. 12 bari
<b>Debit aer</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Temperatură mediu</b>	-20 °C to +70 °C
<b>Carcasă</b>	Aluminium, anodised
<b>Filet</b>	Nickel-plated brass
<b>Piese interioare</b>	Stainless steel
<b>Buton, supapă</b>	Hardened, galvanised steel
<b>Material de etanșare</b>	NBR



## Indicație

Not suitable for hitting / pulsating tools.  
Alte date sunt disponibile la cerere.

## Descriere

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Articol

Denumire	Filet de conectare	Racord	Lungime (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24