

# K-PUR-BREMSSPIRALE

PUR brake coil with connection

**HANSA FLEX**

## Свойства

Соединение 1 + 2	Метрическая наружная резьба, цилиндрическая
Норма	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Допуск	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
Температура min.	-40 °C
Температура max.	90 °C
Материал	PUR



## Дополнительная информация

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## Изделие

Наименование	G1 + G2	Внутренний Ø (mm)	Наружный Ø (mm)	Толщина стенок (mm)	Длина (m)	Цвет
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	черный
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	желтый
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	красный
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	черный
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	желтый
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	красный