


# K-MANO ABSPH ZAPF DREH MUF2

Pressure gauge stopcocks, male - loose (rotatable) female

## Свойства

Применение	For all pressure gauges with a flat gasket acc. to DIN 16258
Диапазон давлений	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Температура	Max. +50 °C
Корпус	Brass with a bare metal surface or stainless steel 1.4571
Ручка	Plastic
Контрольный фланец	-



## Указание

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B  
Прочие данные только по запросу.

## Описание

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Дополнительная информация

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Изделие

Наименование	Резьба	PN (бар)	SW (mm)	Материал
K- 07 20 11 17	G 1/2	25	27	Латунь
K- 07 20 11 18	G 1/2	25	27	Латунь