

# K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

**HANSA FLEX**

## Свойства

Рабочая температура	-60 °C to +100 °C (PA 12)
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Длина трубы	3 m
Единица упаковки	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



## Указание

Operating pressure with 2.5 x overpressure safety!

Прочие данные только по запросу.

## Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Изделие

Наименование	Наружный Ø трубы (mm)	Внутренний Ø трубы (mm)	макс. рабочее давление при 20°C (bar)	Цвет
K- 07 10 04 57	12	9	38	синий
K- 07 10 04 59	12	9	38	черный
K- 07 10 04 61	15	12	25	синий
K- 07 10 04 63	15	12	25	черный
K- 07 10 04 65	18	14	28	синий
K- 07 10 04 67	18	14	28	черный
K- 07 10 04 69	22	18	22	синий
K- 07 10 04 71	22	18	22	черный
K- 07 10 04 73	28	23	20	синий
K- 07 10 04 75	28	23	20	черный