

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Свойства

Рабочая температура	-60 °C to +100 °C (PA 12)
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Длина трубы	3 m
Единица упаковки	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



Указание

Operating pressure with 2.5 x overpressure safety!

Прочие данные только по запросу.

Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Изделие

Наименование	Наружный Ø трубы (mm)	Внутренний Ø трубы (mm)	макс. рабочее давление при 20°C (bar)	Цвет
K- 07 10 04 56	12	9	38	синий
K- 07 10 04 58	12	9	38	черный
K- 07 10 04 60	15	12	25	синий
K- 07 10 04 62	15	12	25	черный
K- 07 10 04 64	18	14	28	синий
K- 07 10 04 66	18	14	28	черный
K- 07 10 04 68	22	18	22	синий
K- 07 10 04 70	22	18	22	черный
K- 07 10 04 72	28	23	20	синий
K- 07 10 04 74	28	23	20	черный