
## K-SCHL-AUFROLLER LUFT

Hose reels for compressed air



| Свойства            |  |
|---------------------|--|
| Материал шланга     | Braided polyurethane                         |
| Рабочее давление    | Max. 16 bar; 13.5 x 9.5 mm hose: max. 12 bar |
| Рабочая температура | -20 °C to +60 °C                             |
| Угол качания        | 300°   |





## Указание

Прочие данные только по запросу.

## Описание

For easy mounting on the wall or ceiling. Closed, rugged, impact-resistant housing made of POM, supply/outlet R 1/4 male thread and lightweight, hard-wearing, oil-resistant polyurethane hose. Incl. 2 m feeder hose (not Art. K-07100618).

## Дополнительная информация

Housing of K-07100621, K-07100620 and K-07100618 identical to K-07100614

| Размер шланга    | A  | В   | Длина шланга   |  |
|------------------|--|---|--|--|
|                  | (mm)   | (mm)  | (m)  |  |
| 12 mm x 8 mm     | 394,5  | 436,0   | 7  |  |
| 12 mm x 8 mm     | 361,0  | 390,0   | 10   |  |
| 12 mm x 8 mm     | 394,5  | 436,0   | 16   |  |
| 13,5 mm x 9,5 mm | 394,5  | 436,0   | 14   |  |
|                  | 12 mm x 8 mm<br>12 mm x 8 mm<br>12 mm x 8 mm | (mm)   12 mm x 8 mm 394,5   12 mm x 8 mm 361,0   12 mm x 8 mm 394,5 | (mm)     (mm)       12 mm x 8 mm     394,5     436,0       12 mm x 8 mm     361,0     390,0       12 mm x 8 mm     394,5     436,0 | (mm)     (mm)     (m)       12 mm x 8 mm     394,5     436,0     7       12 mm x 8 mm     361,0     390,0     10       12 mm x 8 mm     394,5     436,0     16 |