

# K-SPIR SCHL

Spiral hose, without fittings

## Свойства

**Применение** Air, gases, oils, greases, fuels, organic and inorganic substances

**Рабочая температура** -40 °C to +100 °C



## Указание

Прочие данные только по запросу.

## Описание

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Изделие

Наименование	Внутренний Ø шланга (mm)	Внешний Ø шланга (mm)	Внешний Ø спирали (mm)	Витки	Max. working pressure resistance at 23°C (bar)	макс. рабочая длина (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

## Принадлежности

**K-DREHBARE VERSCHR KNICK** Swivel adapters with kink protector

**K-STARRE VERSCHRAUBUNG** Rigid adapters with kink protector