# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

## Свойства

| | |
|---|---|
| **Вид подключения** | with kink protector, swivel type |
| **Рабочая температура** | -40 °C to +74 °C |



## Указание

Прочие данные только по запросу.

## Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Изделие

| Наименование | Резьба | Внутренний Ø шланга (mm) | Внешний Ø шланга (mm) | Ø внешнего витка (mm) | Max. working pressure resistance at 23°C (bar) | макс. рабочая длина (m) |
|---|---|---|---|---|---|---|
| **K- 07 10 07 43** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 3,0 |
| **K- 07 10 07 44** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 6,0 |
| **K- 07 10 07 45** | G 1/4 | 6,3 | 9,5 | 42 | 14 | 7,5 |
| **K- 07 10 07 46** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 3,0 |
| **K- 07 10 07 47** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 6,0 |
| **K- 07 10 07 48** | G 3/8 | 8,0 | 12,0 | 55 | 14 | 7,5 |

## Принадлежности

| | |
|---|---|
| **K-DREHBARE VERSCHRAUBUNG** | Swivel adapters |

*Несмотря на тщательную проверку мы не может исключить ошибки, поэтому мы не берем на себя ответственность за содержащуюся информацию.*