


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Свойства

Рабочее давление	0 - 35 bar, maximum static working pressure (non-pulsating)
Расход воздуха	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Температура среды	-20 °C to +100 °C
Гильза разблокировки	Anodised aluminium
Пружина, пружинное стопорное кольцо, шары	stain less steel
Набивочный материал	Нитрильный каучук



Указание

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Прочие данные только по запросу.

Описание

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Изделие

Наименование	Соединение	Цвет	Длина (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	зеленый	45,0	14
K- 07 35 06 81	G 1/4 male	зеленый	47,0	17
K- 07 35 06 82	G 1/8 female	зеленый	45,0	14
K- 07 35 06 83	G 1/4 female	зеленый	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	синий	45,0	14
K- 07 35 06 89	G 1/4 male	синий	47,0	17
K- 07 35 06 90	G 1/8 female	синий	45,0	14
K- 07 35 06 91	G 1/4 female	синий	47,0	17
K- 07 35 06 92	G 1/8 male	красный	45,0	14
K- 07 35 06 93	G 1/4 male	красный	47,0	17
K- 07 35 06 94	G 1/8 female	красный	45,0	14
K- 07 35 06 95	G 1/4 female	красный	47,0	17