


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Свойства

Рабочее давление	0 - 35 bar, maximum static working pressure (non-pulsating)
Расход воздуха	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Температура среды	-20 °C to +100 °C
Корпус	Brass
Клапан	Die-cast zinc, nickel-plated
Гильза разблокировки	Anodised aluminium
Пружина, пружинное стопорное кольцо, шары	stain less steel
Набивочный материал	Нитрильный каучук



Указание

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Прочие данные только по запросу.

Описание

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Изделие

Наименование	Соединение	Цвет	Длина (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	зеленый	57,5	19
K- 07 35 08 02	G 3/8 male	зеленый	57,5	19
K- 07 35 08 03	G 1/4 female	зеленый	55,5	19
K- 07 35 08 04	G 3/8 female	зеленый	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	синий	57,5	19
K- 07 35 08 10	G 3/8 male	синий	57,5	19
K- 07 35 08 11	G 1/4 female	синий	55,5	19
K- 07 35 08 12	G 3/8 female	синий	54,5	19
K- 07 35 08 13	G 1/4 male	красный	57,5	19
K- 07 35 08 14	G 3/8 male	красный	57,5	19
K- 07 35 08 15	G 1/4 female	красный	55,5	19
K- 07 35 08 16	G 3/8 female	красный	54,5	19