

K-INLINE-EJEKTOREN VR

Inline ejectors »VR«, screw connection

HANSA FLEX

Свойства

Свойства Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
\nlow noise

Применение by screwing / plugging into the distribution beam
direct attachment to the suction pad
for handling various workpieces

Корпус Aluminium eloxed (type VR)

Система форсунок Brass (type VR)

Соединение Вставное соединение



Указание

Прочие данные только по запросу.

Описание

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Изделие

Наименование	Размер форсунок	Подключение к системе вытяжной вентиляции	Подключение системы сжатого воздуха	Вакуумное соединение	Степень разрежения	Расход воздуха при всасывании (L/min)	макс. скорость откачки (L/min)	Длина (mm)	Рабочее давление (bar)
K- 07 45 01 29	0,7	M 5 male	G 1/4 IG	G1/8 female	90 %	21,0	14,0	35,0	5,0
K- 07 45 01 30	0,9	M 5 male	G 1/4 IG	G1/8 female	89 %	36,0	21,0	35,0	5,0