


K-KOMPAKTEJEKTOREN MINI

Mini-compact ejectors

HANSA**FLEX**

Свойства

Свойства	Vacuum generator with integrated control valves and system monitoring functions Gripping and blowing off can be controlled without the need for external valves Optimised air consumption thanks to many models with differing suction capacities Minimum energy costs in continuous operation Easy adjustment with foil keypad, LED display of the settings Minimum size and low weight Optimum vacuum generation directly on the suction pad Complete solution for very simple installation Short learning curve thanks to "teach" function No need for additional sensors Easily visible status indication
-----------------	---



Применение	Ideal where space is restricted and for highly dynamic movements, handling with industrial robots, linear axes pick-and-place systems
Степень разрежения	85 %
Основные части	Anodised aluminium
Встроенный	NC blow-off valve, filter, silencer, non-return valve

Указание

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Прочие данные только по запросу.

Описание

Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Дополнительная информация

Important: Order two connection plugs per ejector.

Изделие

Наименование	Размер форсунки	Состояние покоя всасывающего клапана	Подключение системы сжатого воздуха	Вакуумное соединение	Расход воздуха при всасывании (L/min)	макс. скорость откачки (L/min)	Размер	Рабочее давление (bar)
K-07 45 01 46	1,0	NC	M 5 IG	M5 female	46,0	23,0	65mm x 10mm x 107mm	4,5
K-07 45 01 45	1,0	NO	M 5 IG	M5 female	46,0	23,0	65mm x 10mm x 107mm	4,5

Принадлежности

K-ANSCHLUSSSTECK MAGNETVE 1	Connection plug for solenoid valves
K-ERSATZSCHALDAEMPFER	Replacement silencers
K-ERSATZFILTERELEMENTE 1	Replacement filter element