

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Свойства

Применение	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Температура min.	0 °C
Температура max.	80 °C
Подключение вытяжки	M 3 female
Исполнение	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Ход пружины	5,0 mm



Указание

Прочие данные только по запросу.

Описание

Suitable for all round or oval suction pads in our standard range.

Изделие

Наименование	Вакуумное соединение	Длина (mm)	Вертикальная нагрузка (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400