



# K-DRUCKSCHALTER VAKUUM

Combined vacuum/pressure switch

**HANSA FLEX**

## Свойства

Модель	PNP
Подключение измеряемой среды	G 1/8 male and M 5 female
Гистерезис	Adjustable: 3 to 25% of set value
Область температур	0 - 50 °C
Рабочие среды	Non-aggressive gases. dry, oil-free air
Корпус	Polycarbonate
Выходной сигнал	Analogue: 1 to 5 V
Подключение к электросети	Male connector M8, four pin
Коммутационная способность	125 mA
Потребление тока	30 mA
Индикация состояния	LED



## Указание

Прочие данные только по запросу.

## Описание

Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

## Изделие

Наименование	G1 наружная	G2 внутренняя	G3 наружная	L (mm)	L1 (mm)	Диапазон измерений	Напряжение
K- 07 45 01 31	G 1/8	M 5	M 8 x 1	44,0	62,0	-1 bis +10 bar	10.8 - 30 V DC