
K-3 BKR T DOPPELWIRKEND T1

Stainless steel ball valves, 3-way, with double-acting actuator, T-bore, normal position T1



0				
Свойства				
Модель	Pneumatic actuators, in double- or single acting version, with integrated endposition feedback			
Отверстие	Т-образная форма			
Рабочее давление	max. 63 bar (depending on temperature and nominal size)			
Рабочая температура	-20 °C to +70 °C			
Угол поворота	90 °			
Стандартизированные интерфейсы	Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S			
Управляющее давление	5.5 bar			
Адаптер для клапана	Acc. to NAMUR			
Привод	aluminium eloxed			
Уплотнение привода	NBR			
этпотнение привода	HEIL			
Шаровой кран	Stainless steel 1.4401,with ISO-flange plate			





Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Прочие данные только по запросу.

Описание

3-way cock, reduced bore

Дополнительная информация

Other T-positions on request

Изделие									
Наименование	DN	Резьба	Положение	A (mm)	B (mm)	D (mm)	L (mm)	SW (mm)	
K- 07 30 02 99	15	Rp 1/2	T 1	116,0	130,0	20,0	73,0	27	
K- 07 30 03 01	20	Rp 3/4	T 1	116,0	136,0	23,0	80,0	32	
K- 07 30 03 03	25	Rp 1	T 1	133,0	148,5	28,5	90,0	41	
K- 07 30 03 05	32	Rp 1 1/4	T 1	133,0	153,5	36,5	90,0	50	
K- 07 30 03 07	40	Rp 1 1/2	T 1	137,0	173,0	37,0	105,0	55	
K- 07 30 03 09	50	Rp 2	T 1	161,0	196,5	47,5	115,0	71	