
K-W90 STUECK IG IG 2

Elbows, female-female



Свойства	
Рабочее давление	60 bar
Рабочая температура	Max. 150 °C
Резьба внутренняя	Parallel to DIN EN ISO 228-1
Материал	Brass with a bare metal surface





Указание

Прочие данные только по запросу.

Наименование Резьба L1 (mm) (mm) L2 (mm) SW K- 07 40 11 28 G 1/8 21,0 21,0 10 mm K- 07 40 11 29 G 1/4 25,5 25,5 13 mm K- 07 40 11 30 G 3/8 28,0 28,0 17 mm K- 07 40 11 31 G 1/2 33,5 33,5 21 mm K- 07 40 11 38 G 3/4 36,5 36,5 25 mm	элие				
K- 07 40 11 29 G 1/4 25,5 25,5 13 mm K- 07 40 11 30 G 3/8 28,0 28,0 17 mm K- 07 40 11 31 G 1/2 33,5 33,5 21 mm	енование	Резьба			SW
K- 07 40 11 30 G 3/8 28,0 28,0 17 mm K- 07 40 11 31 G 1/2 33,5 33,5 21 mm	40 11 28	G 1/8	21,0	21,0	10 mm
K- 07 40 11 31 G 1/2 33,5 33,5 21 mm	40 11 29	G 1/4	25,5	25,5	13 mm
22.22.22.22.22.22.22.22.22.22.22.22.22.	40 11 30	G 3/8	28,0	28,0	17 mm
K- 07 40 11 38 G 3/4 36,5 36,5 25 mm	40 11 31	G 1/2	33,5	33,5	21 mm
	40 11 38	G 3/4	36,5	36,5	25 mm
K- 07 40 11 39 G 1 45,0 45,0 30 mm	40 11 39	G 1	45,0	45,0	30 mm