


K-XVMK 6

Male connectors, conical male thread acc. to ISO 7-1

HANSA FLEX

Свойства

Диапазон давлений	Max. 60 bar
Температура	Max. 150 °C
Материал	Никелированная латунь



Указание

Прочие данные только по запросу.

Изделие

Наименование	Наружный Ø трубы	Резьба	L1 (mm)	SW	SW1 (mm)
K- 07 40 20 02	4 mm	R 1/8	27,0	10 mm	10
K- 07 40 20 03	6 mm	R 1/8	28,0	12 mm	12
K- 07 40 20 04	8 mm	R 1/8	29,5	12 mm	14
K- 07 40 20 05	6 mm	R 1/4	32,5	14 mm	12
K- 07 40 20 06	8 mm	R 1/4	33,0	14 mm	14
K- 07 40 20 07	10 mm	R 1/4	37,5	17 mm	19
K- 07 40 20 08	8 mm	R 3/8	33,0	17 mm	14
K- 07 40 20 09	10 mm	R 3/8	38,0	17 mm	19
K- 07 40 20 13	12 mm	R 3/8	39,0	19 mm	22
K- 07 40 20 18	10 mm	R 1/2	40,5	22 mm	19
K- 07 40 20 19	12 mm	R 1/2	41,0	22 mm	22
K- 07 40 20 28	18 mm	R 1/2	43,0	26 mm	32