
K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Свойства	
Область температур	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)
Рабочие среды	Air, neutral gases, water, oil
Диапазон давлений	Vacuum (max. 8 bar)
Настройка	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
Свойства Failsafe	Tight closure in case of loss of voltage
Корпус, седло клапана	Brass
Внутренние детали	Stainless steel
Клапанная тарелка	FKM
Набивочный материал	FKM





Указание

Прочие данные только по запросу.

Описание

Дополнительная информация

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Наименование	Соединение	DN	макс. перепад рабочего давления (bar)	A (mm)	В	C (mm)
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0