## K-STECKERVERSTAERKER

Plug amplifier (mounting directly on the valve)



Свойства	
Номинальное напряжение	24 V DC
Область температур	-10 °C to +75 °C (plug amplifier), -10 °C to +60 °C (chopper amplifier)
Корпус	PA



## Указание

Прочие данные только по запросу.

## Описание

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. <a href="https://document.com/stepless-adjustment">https://document.com/stepless-adjustment of these parameters is vital.</a><a href="https://document.com/stepless-adjustment">https://document.com/stepless-adjustment of these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document.com/stepless-adjustment-of-these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document.com/stepless-adjustment-of-these parameters is vital.</a><a href="https://document.com/stepless-adjustment-of-these parameters is vital.">https://document-of-these parameters is vital.</a><a href="https://document-of-these parameters-of-these par

Изделие	
Наименование	для устройств с подключением
K- 07 25 09 99	G 1/8
K- 07 25 10 00	G 1/4 , G 3/8