

# K-WTEH 2-TLG PC-BEHAEL MANO STAN-MI

Service units, 2-piece with polycarbonate bowl and pressure gauge

**HANSA FLEX**

## Свойства

|                                   |  |
|-----------------------------------|--|
| Входное давление                  | Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)                             |
| Температура среды                 | max. 60 °C   |
| Температура окружающей среды      | Max. 60 °C   |
| Расход                            | 350 l/min (2-piece), 300 l/min (3-piece)   |
| Размер пор в фильтрующем элементе | 5 µm   |
| Набивочный материал               | Нитрильный каучук  |
| Корпус                            | Die-cast zinc, painted silver  |
| Капельная насадка                 | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)                                   |
| Drain valve                       | Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl |
| Измерение расхода воздуха         | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar                         |



## Указание

Прочие данные только по запросу.

## Описание

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Изделие

| Наименование   | Резьба | Диапазон регулирования | A (mm) | B        | C (mm) | D (mm) | DN |
|----------------|--------|------------------------|--------|----------|--------|--------|----|
| K- 07 25 14 89 | G 1/8  | 0.5 - 10 bar           | 85,0   | 167,0 mm | 65,0   | 102,0  | 5  |
| K- 07 25 14 91 | G 1/4  | 0.5 - 10 bar           | 85,0   | 167,0 mm | 65,0   | 102,0  | 5  |

## Запасные части

|                                |   |
|--------------------------------|---|
| K-HALTERBAUSATZ                | Holder  |
| K-SCHALTAFELMUTTER             | Nut   |
| K-ERSATZBEHAELTER MULTI MINI   | Spare tank »multifix-mini« & »standard-mini«              |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter                                 |
| K-VERSCHLEI-SATZ               | Set of wearing parts                                      |
| K-FILTERELEMENT                | Filter element  |
| K-AUTOMAT ABLASSVENTIL         | Automatic drain valve                                     |
| K-TROPFAUFSATZ POLYCARBO       | Drip attachment polycarbonate                             |
| K-TROPFAUFSATZ METALL          | Drip attachment metal                                     |
| K-LOESBARE DOPPELNIPPEL MS     | Double nipples  |
| K-XV AGM MS NI                 | Double nipples, parallel male thread, nickel-plated brass |