

# K-KURZH ZYL EINFACHW

## Short-stroke cylinders, single-acting (magnetic)

### Свойства

|                             |   |
|-----------------------------|---|
| Рабочие среды               | Filtered compressed air, lubricated (ensure continuity) or unlubricated |
| Рабочее давление            | макс. 10 бар  |
| Давление реагирования       | 0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)                        |
| Область температур          | -10 °C to +80 °C  |
| Поршневой шток              | C45 steel, hard chrome-plated   |
| Труба                       | Aluminium alloy, anodised   |
| Диаметр головки             | Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium                      |
| Поршни                      | Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE                    |
| Уплотнение поршневого штока | NBR (additional charge for PU and FKM)                                  |
| Поршневое уплотнение        | NBR (additional charge for PU and FKM)                                  |



### Указание

Прочие данные только по запросу.

### Описание

Suitable for installation in limited spaces, with magnet.

### Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately.

Other types, e.g. increased thermal stability, non-standard strokes, through rod, non-rotating version, etc., available on request.

### Изделие

| Наименование   | Ø поршня | Ход (mm) | Соединение | Резьба поршневого штока внутренняя |
|----------------|----------|----------|------------|------------------------------------|
| K- 07 15 11 87 | 12 mm    | 10       | M 5        | M 3                                |
| K- 07 15 11 88 | 12 mm    | 25       | M 5        | M 3                                |
| K- 07 15 11 89 | 16 mm    | 10       | M 5        | M 5                                |
| K- 07 15 11 90 | 16 mm    | 25       | M 5        | M 5                                |
| K- 07 15 11 91 | 20 mm    | 10       | M 5        | M 5                                |
| K- 07 15 11 92 | 20 mm    | 25       | M 5        | M 5                                |
| K- 07 15 11 93 | 25 mm    | 10       | G 1/8      | M 5                                |
| K- 07 15 11 94 | 25 mm    | 25       | G 1/8      | M 5                                |
| K- 07 15 11 95 | 32 mm    | 10       | G 1/8      | M 6                                |
| K- 07 15 11 96 | 32 mm    | 25       | G 1/8      | M 6                                |
| K- 07 15 11 97 | 40 mm    | 10       | G 1/8      | M 6                                |
| K- 07 15 11 98 | 40 mm    | 25       | G 1/8      | M 6                                |
| K- 07 15 11 99 | 50 mm    | 25       | G 1/8      | M 8                                |
| K- 07 15 12 00 | 63 mm    | 25       | G 1/8      | M 8                                |

### Принадлежности

K-MAGNETSENSOREN-REED Reed magnetic sensor (incl. 2.5 m cable)