
K-STOPPVENTILE IG

Stop valves, ports 2 and 3 with female thread



Свойства				
Рабочее давление	Max. 10 bar			
Управляющее давление	1 - 5 bar, depending on operating pressure			
Температура среды	max. 70 °C			
Расположение	Any. Ring pieces can still be rotated 360° after the valve has been tightened			
Материал	Никелированная латунь			
Набивочный материал	Perbunan			





Указание

Прочие данные только по запросу.

Описание

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Изделие						
Наименование	Port 1	Port 2	Соединение 3	B (mm)	C (mm)	
K- 07 15 20 46	G 1/8	G 1/8	G 1/8	52,0	21,0	
K- 07 15 20 45	G 1/4	G 1/4	G 1/8	58,0	25,0	
K- 07 15 20 47	G 3/8	G 3/8	G 1/8	63,0	31,0	
K- 07 15 20 44	G 1/2	G 1/2	G 1/8	72,0	40,0	