
K-BKR KL SERIE 374

Ball valves, 374 series



Свойства				
Рабочее давление	max. 70 bar (Depending on Temperature)			
Рабочая температура	Max. 150 °C			
Уплотнение	PTFE			
Рукоятка	Stainless steel 1.4301			





Указание

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Прочие данные только по запросу.

Указания по заказу

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Дополнительная информация

G thread acc. DIN EN ISO 228-1

Изделие								
Наименование	DN	Резьба	А	В	L	Материал		
			(mm)	(mm)	(mm)			
K- 07 30 15 32	5	G 1/4	62,0	30,0	47,0	Stainless steel 1.4401/1.4408		
K- 07 30 15 33	7	G 3/8	82,0	30,0	51,0	Stainless steel 1.4401/1.4408		
K- 07 30 15 34	9	G 1/2	92,0	45,0	64,0	Stainless steel 1.4401/1.4408		
K- 07 30 15 35	13	G 3/4	94,0	50,0	68,0	Stainless steel 1.4401/1.4408		