

K-NIPP KUPPL NW7 SCHL MS NI K

Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring

HANSA FLEX

Свойства

| | |
|-------------------|---|
| Рабочее давление | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Температура среды | -20 °C to +100 °C |
| Материал | Никелированная латунь |



Указание

Прочие данные только по запросу.

Изделие

| Наименование | Определение | SW (mm) |
|----------------|--|---------|
| K- 07 35 12 70 | Plug for Hose 6x4 with swivel nut and kink protector spring | - |
| K- 07 35 12 71 | Plug for hose 8x6 with swivel nut and kink protector spring | - |
| K- 07 35 01 90 | Plug for hose 10x8 with swivel nut and kink protector spring | 17 |
| K- 07 35 01 91 | Plug for hose 12x9 with swivel nut and kink protector spring | 17 |

Является дополнительным элементом к следующим изделиям

| | |
|--------------------------|---|
| K-SVKM NW 7,8 AG H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, male |
| K-SVKM NW 7,8 IG H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, female |
| K-SVKM NW 7,8 SCHL TUE H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem |
| K-LKM S NW7,8 AG | Safety couplings DN 7.8, male |
| K-LKM S NW7,8 IG | Safety couplings DN 7.8, female |
| K-LKM S NW7,8 SCHL TUE | Safety couplings DN 7.8, with hose stem |