

K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

HANSA FLEX

Свойства

Рабочее давление	макс. 10 бар
Рабочая температура	-10 °C to +50 °C
Форсунки и удлинители	Thread M12x1.25



Указание

Прочие данные только по запросу.

Описание

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

Изделие

Наименование	Соединение	Соединительная резьба
K- 07 10 00 07	Stem, I.D. 6	G 1/4
K- 07 10 00 10	Stem, I.D. 9	G 1/4
K- 07 10 00 14	Stem, I.D. 13	G 1/4
K- 07 10 00 18	connection nipples for coupling NW 7,2	G 1/4

Принадлежности

K-ZUBEH LP ALU	Accessories for standard blow guns (series 22)
K-FEINSTRAHL DUE LAERMARME M	Low-noise fine-spray nozzles, M12x1.25 connection
K-RUNDDUESE LAERMARME M	Low-noise round nozzles, M12x1.25 connection
K-FLACHDUESE LAERMARME M	Low-noise flat nozzles, M12x1.25 connection
K-STANDARD DUESE	Standard nozzle (short version) with Ø 1.5 mm bore
K-DAEMPFER DUESE	Silencer nozzle, M12x1.25 connection
K-DUESE MIT SCHUTZSCHILD	Nozzle with chip shield, M12x1.25 connection
K-VERL DUESE	Extension nozzles
K-DRUCKREGULIER DUESE	Regulating nozzle, M12x1,25, Safety