

K-RUNDDUESE LAERMARME

Low-noise round nozzles

HANSA FLEX



Указание

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

Описание

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

Изделие

Наименование	Резьба	Длина (мм)	Внешний Ø форсунки (мм)	Материал	Диаграмма
K- 07 10 09 56	G 3/8 male	55,0	11	Nickel-plated brass	3
K- 07 10 09 57	G 3/8 male	50,0	10	Алюминий	4
K- 07 10 09 58	G 1/4 male	41,0	13	Алюминий	5
K- 07 10 09 59	G 1/4 male	46,0	17	Die cast zinc	6
K- 07 10 11 14	G 1/4 male	40,0	17	Plastic (POM)	7
K- 07 10 11 15	G 1/4 male	35,0	11	Алюминий	8
K- 07 10 11 16	G 1/4 male	47,0	19	Die cast zinc	9
K- 07 10 11 17	G 1/4 male	55,0	19	Plastic (ABS)	10