


# K-LKM S NW10 AG

Safety couplings DN 10, Außengewinde

**HANSA FLEX**

## Свойства

Рабочее давление	Max. 16 bar
Расход воздуха	4.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Температура среды	-20 °C to +100 °C
Материал	Galvanised steel / brass
Пружина	Stainless-steel
Набивочный материал	Нитрильный каучук



## Указание

Прочие данные только по запросу.

## Описание

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rate and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414. Suitable for all applications with an above-average air consumption and characterised by extreme conditions.

## Изделие

Наименование	Соединение	Длина (mm)	SW (mm)
K- 07 35 13 06	R 3/8 male	68,0	24
K- 07 35 12 99	R 1/2 male	70,3	24
K- 07 35 13 04	R 3/4 male	60,8	27

## Дополнительные элементы

K-NIPPEL KUPPL NW10 AG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, male
K-NIPPEL KUPPL NW10 IG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, female
K-TUE 1 ST K VZ	Stems for couplings DN 10, hardened, galvanised steel, robust type