K-DRS ELEKTRONISCH

Pressure switches, electronic with digital display

Свойства

Температура окружающей среды	-20 °C to +80 °C
Подключение к электросети	Цилиндрический соединитель M 12 x 1, 4-конт.
Выходной сигнал	2 switching outputs
Точность	1% of span
Вспомогательная энергия	DC 15 - 35V
Детали, контактирующие с измеряемой средой	CrNi steel
Температура измеряемой среды	-20 °C to +85 °C
Технологическое соединение	G 1/4
Степень защиты	IP 65 and IP 67 (M 12 x 1)
Корпус	CrNi steel

Указание

Прочие данные только по запросу.

Описание

Electronic pressure switch with digital display, made of stainless steel, for monitoring and measuring pressures in liquids, gases or compressed air.
Applications: Machine tools, compressors and pumps, hydraulic and pneumatic systems, machinery in general

Изделие

Наименование	Соединение	Диапазон измерений
K- 07 30 30 07	G 1/4	0 - 1.0 bar
K- 07 30 30 12	G 1/4	0 - 2.5 bar
K- 07 30 30 15	G 1/4	0 - 4.0 bar
K- 07 30 30 18	G 1/4	0 - 6.0 bar
K- 07 30 30 08	G 1/4	0 - 10.0 bar
K- 07 30 30 10	G 1/4	0 - 16.0 bar
K- 07 30 30 13	G 1/4	0 - 25.0 bar
K- 07 30 30 16	G 1/4	0 - 40.0 bar
K- 07 30 30 19	G 1/4	0 - 60.0 bar
K- 07 30 30 09	G 1/4	0 - 100.0 bar
K- 07 30 30 11	G 1/4	0 - 160.0 bar
K- 07 30 30 14	G 1/4	0 - 250.0 bar
K- 07 30 30 17	G 1/4	0 - 400.0 bar
K- 07 30 30 20	G 1/4	0 - 600.0 bar

Принадлежности

K-ELEKTRO DRUCHSCHALTER EDS	Electronic pressure switch EDS

Несмотря на тщательную проверку мы не может исключить ошибки, поэтому мы не берем на себя ответственность за содержащуюся информацию.