


K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

HANSA FLEX

Свойства

Рабочее давление	Max. 12 bar, maximum static working pressure (non-pulsating)
Рабочее давление вставных наконечников и ниппеля	0 to 35 bar
Расход воздуха	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Температура среды	-20 °C to +60 °C
Корпус, корпус клапана	Nickel-plated brass
Клапан	Brass
Гильза разблокировки	Plastic
Пружины, пружинное стопорное кольцо, штифты, шары	Stainless steel
Набивочный материал	Нитрильный каучук



Указание

Прочие данные только по запросу.

Описание

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Изделие

Наименование	Соединение	Длина (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

Дополнительные элементы

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,