
K-SCHALLDAE FEDEREINSTELLUNG

Adjustable spring silencers



Свойства	
Рабочее давление	макс. 12 бар
Рабочая температура	-10 °C to +80 °C





Указание

Прочие данные только по запросу.

Резьба	A (mm)	В макс. _(mm)	В мин. _(mm)	SW
G 1/8	12,0	28,0	26,0	13 mm
G 1/4	14,0	32,0	30,0	15 mm
G 3/8	17,0	38,0	36,0	22 mm
G 1/2	17,0	39,0	37,0	22 mm
G 3/4	32,0	50,0	46,0	30 mm
G 1	32,0	50,0	47,0	36 mm
	G 1/8 G 1/4 G 3/8 G 1/2 G 3/4	G 1/8 12,0 G 1/4 14,0 G 3/8 17,0 G 1/2 17,0 G 3/4 32,0	(mm) (mm) G 1/8 12,0 28,0 G 1/4 14,0 32,0 G 3/8 17,0 38,0 G 1/2 17,0 39,0 G 3/4 32,0 50,0	(mm) (mm) (mm) G 1/8 12,0 28,0 26,0 G 1/4 14,0 32,0 30,0 G 3/8 17,0 38,0 36,0 G 1/2 17,0 39,0 37,0 G 3/4 32,0 50,0 46,0