


K-RD MUFFE 246 IG AG

Sockets 246, reducing, female/male

HANSA FLEX

Свойства

| | |
|-----------------------|---|
| Поверхность | Hot dip galvanised |
| Область температур | -20 °C to +300 °C (at 20 bar) |
| Соединительная резьба | acc. ISO 7-1 |
| Материал | Black malleable iron B350-10, design symbol A |
| Допуск | DIN DVGW |



Указание

Прочие данные только по запросу.

Описание

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Дополнительная информация

Further types and dimensions on request.

Изделие

| Наименование | Резьба 1 | Резьба 2 |
|----------------|----------|----------|
| K- 07 40 37 26 | Rp 3/8 | R 1/4 |
| K- 07 40 37 20 | Rp 1/2 | R 1/4 |
| K- 07 40 37 21 | Rp 1/2 | R 3/8 |
| K- 07 40 37 25 | Rp 3/4 | R 1/2 |
| K- 07 40 37 15 | Rp 1 | R 1/2 |
| K- 07 40 37 16 | Rp 1 | R 3/4 |
| K- 07 40 37 19 | Rp 1 1/4 | R 3/4 |
| K- 07 40 37 18 | Rp 1 1/4 | R 1 |
| K- 07 40 37 17 | Rp 1 1/2 | R 1 |
| K- 07 40 37 36 | Rp 1 1/2 | R 1 1/4 |
| K- 07 40 37 22 | Rp 2 | R 1 |
| K- 07 40 37 24 | Rp 2 | R 1 1/4 |
| K- 07 40 37 23 | Rp 2 | R 1 1/2 |
| K- 07 40 51 76 | Rp 2 1/2 | R 2 |
| K- 07 40 51 77 | Rp 3 | R 2 |
| K- 07 40 51 78 | Rp 3 | R 2 1/2 |