

# K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

**HANSA FLEX**

## Свойства

Рабочие среды	Air, neutral gases, filtered
Рабочее давление	0.5 to 10 bar
Рабочая температура	-20 °C to +70 °C
Входит в комплект поставки	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
Корпус	Aluminium, anodised
Материал	Уплотнение: БНК
Набивочный материал	Нитрильный каучук



## Указание

Прочие данные только по запросу.

## Описание

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

## Изделие

Наименование	Функция	Управление	DN	Расход (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650