

K-ZFL VENTILINSEL HDM

Intermediate plates for HDM valve terminal

Свойства

| | |
|-----------------------------------|---|
| Рабочие среды | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Рабочее давление | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Управляющее давление | 3 - 7 bar |
| Область температур | -10 °C to +60 °C |
| Расход | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Количество сигналов управления | Max. 16 (e.g. 16 spring return valves) |
| Ручное вспомогательное управление | Latching (bistable), Monostable (non-latching) version also available on request |
| Потребляемая мощность | 0.6 W per pilot |
| Степень защиты | IP 65 |



Указание

Прочие данные только по запросу.

Описание

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately.

Изделие

| Наименование | Функция |
|----------------|--|
| K- 07 15 22 51 | With additional pilots and exhausts |
| K- 07 15 22 52 | With separate pilots (for multi-pressure systems) |
| K- 07 15 22 44 | With separate exhausts (for multi-pressure system) |