


# K-T-STECK VERS DRE AG-K BE 1

Male branch tees, swivel type, conical male thread, coated

**HANSA FLEX**

## Свойства

|                     |                       |
|---------------------|-----------------------|
| Рабочее давление    | Max. 16 bar           |
| Рабочая температура | -20 °C to +150 °C     |
| Материал            | Никелированная латунь |
| Прижимное кольцо    | Nickel-plated brass   |
| Зажимное кольцо     | Stainless steel       |



## Указание

Прочие данные только по запросу.

## Описание

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Изделие

| Наименование   | Резьба | для наружного Ø шланга | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|--------|------------------------|------------|------------|-------|
| K- 07 40 28 18 | R 1/8  | 4 mm                   | 40,0       | 20,0       | 13 mm |
| K- 07 40 28 19 | R 1/8  | 6 mm                   | 43,0       | 20,0       | 13 mm |
| K- 07 40 28 20 | R 1/8  | 8 mm                   | 47,0       | 20,0       | 13 mm |
| K- 07 40 28 16 | R 1/4  | 6 mm                   | 43,0       | 25,0       | 14 mm |
| K- 07 40 28 17 | R 1/4  | 8 mm                   | 47,0       | 25,0       | 14 mm |
| K- 07 40 28 15 | R 1/4  | 10 mm                  | 53,0       | 26,0       | 16 mm |
| K- 07 40 28 21 | R 3/8  | 8 mm                   | 47,0       | 28,0       | 18 mm |
| K- 07 40 48 02 | R 3/8  | 10 mm                  | 53,0       | 30,0       | 18 mm |
| K- 07 40 48 03 | R 3/8  | 12 mm                  | 58,0       | 32,5       | 20 mm |
| K- 07 40 48 01 | R 1/2  | 12 mm                  | 58,0       | 35,5       | 22 mm |