
K-SCHOTTVERB POLYPROPYLEN

Bulkhead couplings - polypropylene



Свойства			
Рабочее давление	Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 2.5 bar (at 90 °C)		
Материал	Polypropylene (PP)		
Рабочая температура	Max. 90 °C		





Указание

Прочие данные только по запросу.

Описание

Chemically resistant to almost all inorganic acids and bases, even in high concentrations and at temperatures greater than 90 °C.

изделие

No Adams				
Для шланга	Резьба	L1	SW	
		(mm)		
4 mm / 6 mm	M 10 x 1	53,0	14 mm	
6 mm / 8 mm	M 14 x 1,5	64,0	19 mm	
8 mm / 10 mm	M 16 x 1,5	73,0	22 mm	
9 mm / 12 mm	M 18 x 1,5	84,0	24 mm	
	4 mm / 6 mm 6 mm / 8 mm 8 mm / 10 mm	4 mm / 6 mm M 10 x 1 6 mm / 8 mm M 14 x 1,5 8 mm / 10 mm M 16 x 1,5	4 mm / 6 mm M 10 x 1 53,0 6 mm / 8 mm M 14 x 1,5 64,0 8 mm / 10 mm M 16 x 1,5 73,0	