

K-GMM 2

Glycerine-filled pressure gauges, CrNi steel type

HANSA FLEX

Свойства

Тип	233.30
Исполнение	Glycerine-filled Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Применение	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Класс качества	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Температура среды	max. +100 °C
Температура окружающей среды	от -20 °C до +60 °C
Корпус	CrNi steel
Смотровое стекло	Laminated safety glass Ø 63 = Polycarbonate



Указание

Прочие данные только по запросу.

Изделие

Наименование	Диапазон измерений	Ø (mm)	Соединение
K- 07 20 07 03	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 04	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 05	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 06	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 07	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 08	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 09	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 10	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 11	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 07 12	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 07 13	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 07 14	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 01 79	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 80	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 01 81	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 01 82	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 01 83	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 01 84	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 85	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 86	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 87	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 88	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 89	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 90	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 91	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 01 92	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 01 93	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 94	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 01 95	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 01 96	0 - 600.0 bar	100,0	G 1/2"