K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type



Свойства	
Рабочее давление	макс. 10 бар
Расход воздуха	1.800 l/min (at 6 bar and Δp = 1 bar)
Температура среды	-20 °C to +150 °C
Корпус	Stainless steel 1.4404
Резьба	Stainless steel 1.4404
Внутренние детали	Stainless steel 1.4404
Кнопка, клапан	Stainless steel 1.4404
Набивочный материал	FKM



Указание

Not suitable for hitting / pulsating tools.

Прочие данные только по запросу.

Описание

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Дополнительная информация

Not suitable for hitting / pulsating tools.

Изделие				
Наименование	Соединение	Длина	SW	
K- 07 35 12 79	C 1/4 famala	(mm)	(mm) 21	
K- 07 35 12 79	G 1/4 female	71,5		
	G 3/8 female	75,5	21	
K- 07 35 12 81	G 1/2 female	77,5	24	