

K-STECKVERBINDU ST RED 3

Reducers with push-in plug

HANSA FLEX

Свойства

Рабочее давление	Max. 15 bar, coarse vacuum
Область применения	Air, vacuum
рекомендуемые шланги	PU or PA (nylon)
Рабочие среды	Compressed air and all gases or liquids that are compatible with the materials
Область температур	-20 °C to +80 °C
Материал	Plastic, Nickel plated brass
Прижимное кольцо	Plastic



Указание

Прочие данные только по запросу.

Описание

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Изделие

Наименование	для наружного Ø шланга	L1 (mm)
K- 07 40 03 90	4 mm in (reduced 6 mm out)	39,5
K- 07 40 03 91	4 mm in (reduced 8 mm out)	41,5
K- 07 40 03 92	6 mm in (reduced 8 mm out)	41,5
K- 07 40 03 93	6 mm in (reduced 10 mm out)	46,5
K- 07 40 03 94	6 mm in (reduced 12 mm out)	40,5
K- 07 40 03 95	8 mm in (reduced 10 mm out)	46,8
K- 07 40 03 96	8 mm in (reduced 12 mm out)	46,8
K- 07 40 03 97	10 mm in (reduced 12 mm out)	52,2