
K-STECKVERBINDU 2

Straight push-in connector



Свойства	
Рабочее давление	Max. 16 bar
Рабочая температура	-20 °C to +150 °C
Материал	Никелированная латунь
Прижимное кольцо	Nickel-plated brass
Зажимное кольцо	Stainless steel





Указание

Прочие данные только по запросу.

Описание

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Изделие			
Наименование	для наружного Ø шланга	L1 (mm)	
K- 07 40 27 49	4 mm	31,0	
K- 07 40 27 50	6 mm	33,0	
K- 07 40 27 51	8 mm	37,0	
K- 07 40 27 52	10 mm	39,0	
K- 07 40 47 74	12 mm	43,0	
K- 07 40 40 91	14 mm	47,5	