
K-L-STECK VB

Union elbows



Свойства	
Рабочее давление	Max. 16 bar
Рабочая температура	-20 °C to +150 °C
Материал	Никелированная латунь
Прижимное кольцо	Nickel-plated brass
Зажимное кольцо	Stainless steel





1

Указание

Прочие данные только по запросу.

Описание

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Изделие				
Наименование	для наружного Ø шланга	L1 (mm)	L2 (mm)	
K- 07 40 27 53	4 mm	17,5	17,5	
K- 07 40 27 54	6 mm	20,0	20,0	
K- 07 40 27 55	8 mm	23,0	23,0	
K- 07 40 27 56	10 mm	25,0	25,0	
K- 07 40 47 79	12 mm	27,5	27,5	
K- 07 40 47 80	14 mm	31,0	31,0	