


K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Свойства

Внутренний слой	Soft-PVC, black
Вставка	Оплетка из полиэфира
Наружный слой	Soft-PVC, blue
Температура	-20 °C to +60 °C
Длина рулона	50 m



Указание

Прочие данные только по запросу.

Описание

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Изделие

Наименование	Внутренний Ø шланга (mm)	Внешний Ø шланга (mm)	Max. working pressure resistance at 23°C (bar)	Мин. радиус изгиба (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88